

Specifications		
1.	Cabinet Size	: 700 x 400 x 1600 MM
2.	Charging Gun	: Double Gun Length : 5M
3.	Output Power	: 80 KW
4.	Input Voltage Range	: Three - Phase five-wire input AC380V
5.	Output Voltage Range	: 150-1000 VAC; Output current range: 0-250 A
6.	Communication Interface	: Ethernet, 3G/4G
7.	Display	: 7 inch bright color touch screen
8.	Protection Level	: IP54
9.	Working Temperature	: -25 ~ + 50° C



Fast Charger
GBT/CCS2
EDCL080B



**80 KW vertical DC charging pile double gun
for charging Electric Vehicles.**



ECO AUTO TRADING PVT. LTD.

SOLE DISTRIBUTER

Anamnagar - 29, Kathmandu, Nepal

☎01-5922807 (Office)

☎+977-9708072575 / 9708072576 / 9708072577

Email : info@ecoauto.com.np | Website: ecoauto.com.np



Location Map

Technical Data		
Input	Power Supply	3P+N+PE
	voltage Range	400VAC +- 20%
	Frequency	50/60 Hz
Output	Output Voltage	200-1000V DC
	Maximum Currnet	250 A
	Rated Power	80KW
User Interface	Charger Connector	CCS2 cable or GB/T cable
	Cable Length	5M
	Enclosure	Galvanized steel
	LED Indicator	Green/Yellow/Red
	LCD Display	7" color touch screen
	RFID Reader	Mifare ISO/IEC 14443 A
	Start Mode	Plug & Play/ RFID card/ App
	Emergency Stop	Yes
	Interface Language	English/Chinese
	Auxiliary Power	12 Vde
Communication	WIFI	Optional
	Ethernet	Yes
	3G/4G	Yes
	OCPP	OCPP 1.6 Json(OCPP 2.0 optional)
Electrical Parameter	Efficiency	≥95%
	Power Factor	≥0.99@50%-1-% loading
	THD	≤5%@50%-1-100% loading
	Ripple Factor	≤±0.5%

Technical Data		
Safety	RCD	Type A
	Ingress Protection	IP54
	Impact Protection	1K08
	Certification	CE
	Certificate Compliance	GB/T18487.1-2015, GB/T18487.2-2017, GB/T 34657.1-2017, NB/T 33002-2018, NB/T 33008.2-2018
	Special Protection	Over current protection, Residual current protection, short circuit protection, floor protection, surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection
	Warranty	2 years
Environment	Installation	Floor-standing
	Cooling Method	Fan Cooling
	Noise	≤60dB
	Work Temperature	-30°C to +55°C
	Work Humidity	5% - 95%
	Product Dimensions	926x505x1750(L*W*H) mm
	Packaging Dimensions	926x505x1750(L*W*H) mm
	Net Weight	240 Kg
	Gross Weight	280 Kg